

IMPACT SOCKET WRENCHES 1.1/2"

EGA Master Non-Sparking Tools are the best alternative for applications in potentially explosive environments.



- 1.1/2"
- STANDARD
- MM
- 6 PT.

**Both in mm
and in inches!**

1. We offer different sizes of non-sparking impact socket wrenches.
Square drives in 1/2", 3/4", 1", 1.1/2", and 2.1/2".

2. EGA Master also offers a wide range of Atex Impact Wrenches, the ideal tools for maintenance, construction, and repair operations in explosive atmospheres.



- 12 PT.



COD.	MAT.	COD.	MAT.		L (mm)	Pt	
78133	Cu-Be	78134	Al-Bron	34	80		2200
78135		78136		36			
78137		78138		38			
78139		78140		41	85		2400
78141		78142		46			
78143		78144		48			
78145		78146		50	90		2600
78147		78148		54			
78149		78150		55			
78151		78152		60	95		3050
78153		78154		65			
78155		78156		70	100		3800
78157		78158		75			
78159		78160		80			
78161		78162		85	110	5600	
78163		78164		90	125	6850	
78165		78166		95	130	7650	
78167		78168		100	135	8200	
78169		78170		105	140	8800	

COD.	MAT.	COD.	MAT.		L (mm)	Pt	
78211	Cu-Be	78212	Al-Bron	34	80	2200	
78213		78214		36			
78215		78216		38			
78217		78218		41	85	2400	
78219		78220		46			
78221		78222		48			
78223		78224		50	90	2600	
78225		78226		54			
78227		78228		55			
78229		78230		60	95	3050	
78231		78232		65			
78233		78234		70	105	3800	
78235		78236		75			
78237		78238		80	115	4800	
78239		78240		85			
78241		78242		90	125	6850	
78243		78244		95			
78245		78246		100	130	8200	
78247		78248		105			

■ 1.1/2"

■ STANDARD

■ INCH

■ 6 PT.



■ 12 PT.



COD.	MAT.	COD.	MAT.		L (mm)	Pt	
78171	Cu-Be	78172	Al-Bron	1.3/8	80	6	2200
78173		78174		1.5/8			2400
78175		78176		1.13/16	85	2600	
78177		78178		2		2650	
78179		78180		2.1/8	90	3050	
78181		78182		2.3/8		3300	
78183		78184		2.1/2	95	3350	
78185		78186		2.9/16		3400	
78187		78188		2.5/8	100	3800	
78189		78190		2.3/4		4100	
78191		78192		2.15/16	110	4200	
78193		78194		3		4800	
78195		78196		3.1/8	115	5600	
78197		78198		3.3/8		6700	
78199		78200		3.1/2	125	7650	
78201		78202		3.3/4		8200	
78203		78204		3.15/16	130	8800	
78205		78206		4		10000	
78207		78208		4.1/8			
78209		78210		4.1/2			

COD.	MAT.	COD.	MAT.		L (mm)	Pt	
78249	Cu-Be	78250	Al-Bron	1.3/8	80	12	2200
78251		78252		1.5/8			
78253		78254		1.13/16	85	2400	
78255		78256		2		2600	
78257		78258		2.1/8	90	2650	
78259		78260		2.3/8		3050	
78261		78262		2.1/2	95	3300	
78263		78264		2.9/16		3350	
78265		78266		2.5/8	100	3400	
78267		78268		2.3/4		3800	
78269		78270		2.15/16	105	4100	
78271		78272		3		4200	
78273		78274		3.1/8	115	4800	
78275		78276		3.3/8		5600	
78277		78278		3.1/2	125	6700	
78279		78280		3.3/4		7650	
78281		78282		3.15/16	130	8200	
78283		78284		4			
78285		78286		4.1/8		8800	
78287		78288		4.1/2		10000	



TECHNICAL SPECIFICATIONS

MATERIAL	Cu-Be (Beryllium copper) or Al-Bron (Aluminium bronze)
HARDNESS	Cu-Be: 311-408 Brinell Al-Bron: 241-311 Brinell



Llaves de Impacto - Neumáticas e Hidráulicas, Cuadrado 1/2", 3/4", 1" y 1.1/2" para zonas ATEX - Ver capítulo de Seguridad Intrínseca.
Impact Wrenches - Pneumatic and Hydraulic, 1/2", 3/4", 1" and 1.1/2" Sq. Drive for ATEX zones - See Intrinsic Safety chapter.
Douilles à choc - Pneumatiques et Hydrauliques, Carrée de 1/2", 3/4", 1" et 1.1/2" pour zones ATEX - Voir chapitre Sécurité Intrinsèque.