


คัตเตอร์

## Quarter circle cutters DIN 6518 B



Range of application:

Recommended for milling in construction steels, tempered steels and cementation steels with standard tensile strength up to 1.100 N/mm<sup>2</sup> and short-chipping of non-ferrous metals.

Order No. 1464 Art. - Nr.	$r_{H11}$ mm	d1 mm	d2 <sub>H6</sub> mm	d3 mm	L1 mm	4L2 mm	Z
1464001001	1.00	8	10	6	60	10	4
1464001201	1.25	8.5	10	6	60	10	4
1464001501	Δ 1.50	9	10	6	60	10	4
1464001601	1.60	9.2	10	6	60	10	4
1464002001	2.00	10	10	6	60	15	4
1464002501	2.50	11	10	6	60	15	4
1464003001	3.00	12	12	6	60	11	4
1464003501	Δ 3.50	13	12	6	60	11	4
1464004001	4.00	14	12	6	60	11	4
1464004501	Δ 4.50	15	12	6	60	11	4
1464005001	5.00	16	12	6	60	11	4
1464005501	Δ 5.50	19	16	8	67	14	4
1464006001	6.00	20	16	8	67	14	4
1464006301	6.30	20.6	16	8	71	18	4
1464006501	Δ 6.50	21	16	8	71	18	4
1464007001	Δ 7.00	22	16	8	71	18	4
1464007501	Δ 7.50	23	16	8	71	18	4
1464008001	8.00	24	16	8	71	18	4
1464010001	10.00	28	25	8	85	22	4
1464012001	12.00	34	25	10	90	27	4
1464012501	12.50	41	25	16	100	32	6
1464015001	Δ 15.00	46	25	16	100	32	6
1464016001	16.00	48	25	16	100	32	6
1464020001	20.00	56	32	16	112	40	6

Δ Intermediate radii