

CUTTER

คัตเตอร์



ใบเลื่อยวงเดือนตัดเหล็ก รุ่น FMA, TFMA


SCREW SLOTTING CUTTERS 70Dia. (56NT) NON-COATED AND TiN COATED



FMA



TFMA



※ There is a key way

Tolerance of thickness (T)

Thickness	Tolerance
From 0.5 to 3.0	±0.02
5.0 or less exceeding 3.0	±0.024




• For slitting process

Order No.	Order No.	Size			
		Diameter	Thickness	Hole Dia.	Number of teeth
		D	T	d	NT
FMA005	TFMA005	70	0.5	25.4	56
FMA006	TFMA006	70	0.6	25.4	56
FMA007	TFMA007	70	0.7	25.4	56
FMA008	TFMA008	70	0.8	25.4	56
FMA009	TFMA009	70	0.9	25.4	56
FMA010	TFMA010	70	1.0	25.4	56
FMA011	TFMA011	70	1.1	25.4	56
FMA012	TFMA012	70	1.2	25.4	56
FMA013	TFMA013	70	1.3	25.4	56
FMA014	TFMA014	70	1.4	25.4	56
FMA015	TFMA015	70	1.5	25.4	56
FMA016	TFMA016	70	1.6	25.4	56
FMA017	TFMA017	70	1.7	25.4	56
FMA018	TFMA018	70	1.8	25.4	56
FMA019	TFMA019	70	1.9	25.4	56
FMA020	TFMA020	70	2.0	25.4	56
FMA021	TFMA021	70	2.1	25.4	56
FMA022	TFMA022	70	2.2	25.4	56
FMA023	TFMA023	70	2.3	25.4	56
FMA024	TFMA024	70	2.4	25.4	56
FMA025	TFMA025	70	2.5	25.4	56
FMA026	TFMA026	70	2.6	25.4	56
FMA027	TFMA027	70	2.7	25.4	56

Order No.	Order No.	Size			
		Diameter	Thickness	Hole Dia.	Number of teeth
		D	T	d	NT
FMA028	TFMA028	70	2.8	25.4	56
FMA029	TFMA029	70	2.9	25.4	56
FMA030	TFMA030	70	3.0	25.4	56
FMA031	TFMA031	70	3.1	25.4	56
FMA032	TFMA032	70	3.2	25.4	56
FMA033	TFMA033	70	3.3	25.4	56
FMA034	TFMA034	70	3.4	25.4	56
FMA035	TFMA035	70	3.5	25.4	56
FMA036	TFMA036	70	3.6	25.4	56
FMA037	TFMA037	70	3.7	25.4	56
FMA038	TFMA038	70	3.8	25.4	56
FMA039	TFMA039	70	3.9	25.4	56
FMA040	TFMA040	70	4.0	25.4	56
FMA041	TFMA041	70	4.1	25.4	56
FMA042	TFMA042	70	4.2	25.4	56
FMA043	TFMA043	70	4.3	25.4	56
FMA044	TFMA044	70	4.4	25.4	56
FMA045	TFMA045	70	4.5	25.4	56
FMA046	TFMA046	70	4.6	25.4	56
FMA047	TFMA047	70	4.7	25.4	56
FMA048	TFMA048	70	4.8	25.4	56
FMA049	TFMA049	70	4.9	25.4	56
FMA050	TFMA050	70	5.0	25.4	56

Dia. (mm)	Axial run-out						
	Thickness (T)						
	0.4 or less	0.6 or less exceeding 0.4	1.0 or less exceeding 0.6	1.6 or less exceeding 1.0	2.5 or less exceeding 1.6	4.0 or less exceeding 2.5	5.0 or less exceeding 4.0
45	0.16	0.12	0.1	0.08	0.06	0.05	-
70	-	0.16	0.12	0.1	0.08	0.06	0.05

ใบเลื่อยวงเดือนคม 3 หน้า พันตรง รุ่น SC SIDE MILLING CUTTERS



※ Key way non only Hole Dia. Ø15.875

Tolerance of thickness (T)

Thickness	Tolerance
3.0 or less	+0.060 0
6.0 or less exceeding 3.0	+0.075 0
10.0 or less exceeding 6.0	+0.090 0
18.0 or less exceeding 10.0	+0.110 0
30.0 or less exceeding 18.0	+0.130 0
50.0 or less exceeding 30.0	+0.160 0



• Wide variety of diameters and thickness

• Slitting, step cutting, side milling

• Uses MCO material (Cobalt high-speed steel)