

Order No.	Order No.	Size			
		Diameter	Thick-ness	Hole Dia.	Number of teeth
		D	T	d	NT
<b>MSV250X045</b>	<b>TMSV250X045</b>	250	4.5	31.75	84
<b>MSV250X050</b>	<b>TMSV250X050</b>	250	5.0	31.75	84
<b>MSV250X055</b>	<b>TMSV250X055</b>	250	5.5	31.75	84
<b>MSV250X060</b>	<b>TMSV250X060</b>	250	6.0	31.75	84
<b>MSV250X070</b>	<b>TMSV250X070</b>	250	7.0	31.75	84

Order No.	Order No.	Size			
		Diameter	Thick-ness	Hole Dia.	Number of teeth
		D	T	d	NT
<b>MSV250X080</b>	<b>TMSV250X080</b>	250	8.0	31.75	84
<b>MSV300X030</b>	<b>TMSV300X030</b>	300	3.0	31.75	102
<b>MSV300X040</b>	<b>TMSV300X040</b>	300	4.0	31.75	102
<b>MSV300X050</b>	<b>TMSV300X050</b>	300	5.0	31.75	100
<b>MSV300X060</b>	<b>TMSV300X060</b>	300	6.0	31.75	100

### Axial run-out of Metal Slitting Saws

Dia. (mm)	Axial run-out							
	Thickness (T)							
	0.4 or less	0.6 or less exceeding 0.4	1.0 or less exceeding 0.6	1.6 or less exceeding 1.0	2.5 or less exceeding 1.6	4.0 or less exceeding 2.5	6.0 or less exceeding 4.0	8.0 or less exceeding 6.0
75	0.2	0.16	0.12	0.11	0.08	0.06	0.05	0.04
100, 125	-	0.20	0.16	0.12	0.1	0.08	0.06	0.05
150, 175, 200	-	-	0.2	0.16	0.12	0.1	0.08	0.06
250, 300	-	-	-	-	0.16	0.12	0.1	0.08

CUTTER

คัตเตอร์

Cutter  
คัตเตอร์

### ใบเลื่อยวงเดือนตัดเหล็ก รุ่น SFM, TSFM


### SCREW SLOTTING CUTTERS (45Dia.) NON-COATED AND TiN COATED



SFM



TSFM



※ Key way none



Tolerance of thickness (T)

Thickness	Tolerance
From 0.3 to 3.0	±0.02
4.0 or less exceeding 3.0	±0.024



• For slitting small works

Order No.	Order No.	Size			
		Diameter	Thickness	Hole Dia.	Number of teeth
		D	T	d	NT
<b>SFM003</b>	<b>TSFM003</b>	45	0.3	15.875	90
<b>SFM004</b>	<b>TSFM004</b>	45	0.4	15.875	90
<b>SFM005</b>	<b>TSFM005</b>	45	0.5	15.875	90
<b>SFM006</b>	<b>TSFM006</b>	45	0.6	15.875	90
<b>SFM007</b>	<b>TSFM007</b>	45	0.7	15.875	90
<b>SFM008</b>	<b>TSFM008</b>	45	0.8	15.875	90
<b>SFM009</b>	<b>TSFM009</b>	45	0.9	15.875	90
<b>SFM010</b>	<b>TSFM010</b>	45	1.0	15.875	90
<b>SFM011</b>	<b>TSFM011</b>	45	1.1	15.875	90
<b>SFM012</b>	<b>TSFM012</b>	45	1.2	15.875	90
<b>SFM013</b>	<b>TSFM013</b>	45	1.3	15.875	90
<b>SFM014</b>	<b>TSFM014</b>	45	1.4	15.875	90
<b>SFM015</b>	<b>TSFM015</b>	45	1.5	15.875	90
<b>SFM016</b>	<b>TSFM016</b>	45	1.6	15.875	90
<b>SFM017</b>	<b>TSFM017</b>	45	1.7	15.875	90
<b>SFM018</b>	<b>TSFM018</b>	45	1.8	15.875	90
<b>SFM019</b>	<b>TSFM019</b>	45	1.9	15.875	90
<b>SFM020</b>	<b>TSFM020</b>	45	2.0	15.875	90
<b>SFM021</b>	<b>TSFM021</b>	45	2.1	15.875	90

Order No.	Order No.	Size			
		Diameter	Thickness	Hole Dia.	Number of teeth
		D	T	d	NT
<b>SFM022</b>	<b>TSFM022</b>	45	2.2	15.875	90
<b>SFM023</b>	<b>TSFM023</b>	45	2.3	15.875	90
<b>SFM024</b>	<b>TSFM024</b>	45	2.4	15.875	90
<b>SFM025</b>	<b>TSFM025</b>	45	2.5	15.875	90
<b>SFM026</b>	<b>TSFM026</b>	45	2.6	15.875	90
<b>SFM027</b>	<b>TSFM027</b>	45	2.7	15.875	90
<b>SFM028</b>	<b>TSFM028</b>	45	2.8	15.875	90
<b>SFM029</b>	<b>TSFM029</b>	45	2.9	15.875	90
<b>SFM030</b>	<b>TSFM030</b>	45	3.0	15.875	90
<b>SFM031</b>	<b>TSFM031</b>	45	3.1	15.875	90
<b>SFM032</b>	<b>TSFM032</b>	45	3.2	15.875	90
<b>SFM033</b>	<b>TSFM033</b>	45	3.3	15.875	90
<b>SFM034</b>	<b>TSFM034</b>	45	3.4	15.875	90
<b>SFM035</b>	<b>TSFM035</b>	45	3.5	15.875	90
<b>SFM036</b>	<b>TSFM036</b>	45	3.6	15.875	90
<b>SFM037</b>	<b>TSFM037</b>	45	3.7	15.875	90
<b>SFM038</b>	<b>TSFM038</b>	45	3.8	15.875	90
<b>SFM039</b>	<b>TSFM039</b>	45	3.9	15.875	90
<b>SFM040</b>	<b>TSFM040</b>	45	4.0	15.875	90

### Axial run-out of Metal Slitting Saws

Dia. (mm)	Axial run-out							
	Thickness (T)							
	0.4 or less	0.6 or less exceeding 0.4	1.0 or less exceeding 0.6	1.6 or less exceeding 1.0	2.5 or less exceeding 1.6	4.0 or less exceeding 2.5	5.0 or less exceeding 4.0	
45	0.16	0.12	0.1	0.08	0.06	0.05	-	
70	-	0.16	0.12	0.1	0.08	0.06	0.05	