


END MILL

ดอกเอ็นมิลล์



ดอกเอ็นมิลล์ EPOCH SUS WAVE EPSWL4 -PN



Long



0 ~ -0.05



h5



h6

$D_s \leq 6$: 0 ~ -0.005
 $6 < D_s \leq 10$: 0 ~ -0.006
 $10 < D_s \leq 12$: 0 ~ -0.008
 $D_s = 16$: 0 ~ -0.011
 $D_s = 20$: 0 ~ -0.013

(mm)

For stable cutting of stainless steel in environments using low-rigidity machines and weak clamps.

Item Code	Stock	Size (mm)					Corner chamfering width	No. of flutes	Type
		Dc Tool Dia.	l Flute Length	L Overall length	Ds Shank Dia.				
EPSWL4060-PN	●	6	30	70	6	0.4	4	B	
EPSWL4070-PN	□	7	35	80	8	0.4	4	A	
EPSWL4080-PN	●	8	40	80	8	0.5	4	B	
EPSWL4090-PN	□	9	45	100	10	0.5	4	A	
EPSWL4100-PN	●	10	50	100	10	0.5	4	B	
EPSWL4110-PN	□	11	55	120	12	0.5	4	A	
EPSWL4120-PN	●	12	60	120	12	0.5	4	B	
EPSWL4130-PN	□	13	65	130	16	0.7	4	A	
EPSWL4140-PN	□	14	70	130	16	0.7	4	A	
EPSWL4150-PN	□	15	75	130	16	0.7	4	A	
EPSWL4160-PN	●	16	80	135	16	0.7	4	B	
EPSWL4170-PN	□	17	85	135	20	0.7	4	A	
EPSWL4180-PN	□	18	90	145	20	0.7	4	A	
EPSWL4190-PN	□	19	95	145	20	0.7	4	A	
EPSWL4200-PN	●	20	100	155	20	0.7	4	B	

□ : Stocked by specified distributor. Contact with our sales department.

● : Stocked item

Please refer to page 652 for Condition